


FEATURES

- Ultra low profile design can be used in a wide variety of applications
- Diverse controls compatibilities provide ease of mind in useability
- Multiple options for easy mounting and installation
- End to end illumination using a dependable light engine with an L70 of greater than 150,000 hours
- Expanse of light engine choices in addition to several possible options and adders
- Color Tuning and RGBW available with correlating controls packages



SPECIFICATIONS

CONSTRUCTION

- Pre painted white steel utilizing screw fasteners for gear tray attachment
- Several back of fixture pre punches for ease of installation

MOUNTING & INSTALLATION

- Suspended or surface mount
- Connection brackets upon request to be used for end to end applications
- Available suspension and surface mount installation kits for various ceiling styles ; exposed, acoustical, sheetrock

OPTICAL

- Evenly diffuse extruded acrylic lens
- Wide distribution due to wrap around curved lens

ELECTRICAL

- LED Light Engine designed for reliability and long life operation
- Standard 0-10V dimming to 1% with other standards available
- 120 / 277 compatible with other voltages available


CONTROLS

- Individual or grouping control with many brands available
- For further in depth controls integrations, please see page 2

LISTINGS


- DesignLights Consortium qualified, see DLC QPL
- ETL safety certified for damp locations
- GSA Advantage Program qualified

DIMENSIONAL INFORMATION




ADDITIONAL GRAPHICS

REFLECTOR PROFILES



CP
Width 4.75"
Height 2.50"



CL
Width 4.50"
Height 1.50"



RW/RE
Width 4.50"
Height 2.25"



CH
Width 2.25"
Height 4.25"



ORDERING INFORMATION

STYLE	SIZE	LIGHT ENGINE		COLOR TEMP	OPTIONS	OPTIONS (CONTINUED)
F FIXTURE	14MT 1' x 4'	1' X 4'	1' X 8'	35 3500K	FR FROSTED LENS	SD STEP DIMMING (BI LEVEL OR TRI LEVEL)
	18MT 1' x 8'	F4X2 13W 1841 LUMENS	F4L7 27W 3682 LUMENS	40 4000K		LVD120 / 277 120V / 277V LINE VOLTAGE DIMMING
		F4X8 18W 2493 LUMENS	F4N6 36W 4985 LUMENS	50 5000K		D PREWIRED FOR 0-10V DIMMING
		F4L4 24W 3262 LUMENS	F4M6 48W 6525 LUMENS	2765 2700K - 6500K (ADJUSTABLE)		EM EMERGENCY BACKUP INCLUDED (6W STANDARD)
		F4L9 29W 3950 LUMENS	F4H8 58W 7901 LUMENS			DTOAUX DIM TO OFF AND 12V / 24V LED DRIVER
		F4N2 32W 4329 LUMENS	F4V4 64W 8658 LUMENS			LDE1 / LDE5 LUTRON ECOSYSTEM 1% / 5% DIMMING LED DRIVER
		F4N5 35W 4713 LUMENS	F4Y0 70W 9427 LUMENS			L3DA LUTRON 3-WIRE ECOSYSTEM LED DRIVER
		F4M0 40W 5229 LUMENS	F4Z0 80W 10458 LUMENS			PSQ02U LUTRON TUNABLE WHITE T SERIES LED DRIVER
						CT COLOR TUNING WITH VARIOUS CONTROL OPTIONS AVAILABLE

CONTROLS INTEGRATION

ESI is partnered with industry leading vendors to provide numerous different levels of lighting control. Add control code shown below to the end of your desired part number for simple ordering. For any controls desires that are not listed in the below or on our [controls sell sheet](#), please reach out to any member of our sales team.

LUTRON	VDO VIVE FIXTURE CONTROLS - OCCUPANCY & DAYLIGHT / RF ONLY	VRF	LPxEXT LIMELIGHT BY LUTRON RF CONTROLS	
CASAMBI	CBUASR FIXTURE INTEGRATED WIRELESS MESH CONTROLLERS FOR TUNEABLE WHITE AND RGBW CONTROL	CBUPWM4	CBUDCS	XPRESS WIRELESS SCENE CONTROLLER
AVI ON	2110UFL FIXTURE INTEGRATED WIRELESS MESH CONTROLLERS	AVIIFA	AVISENIRW LOW VOLTAGE WIRELESS SENSOR	2402BAT WIRELESS SCENE CONTROLLER
PHILIPS	SNS200 EASYSense FIXTURE MOUNTED LOWBAY OCC SENSORS	SNS300	SNH200 EASYSense HIGHBAY OCCUPANCY SENSOR	
iR TEC	LRD309S INDIVIDUAL CONTROL OCCUPANCY SENSORS	LMD509S	ONLRD209S OS-NET WIRELESS CONTROLS SYSTEM INCLUDING SENSORS AND LINE VOLTAGE POWERED WIRELESS SWITCH	ONLRD509S ONPBD705W



USA DESIGNED • USA MANUFACTURED • USA ASSEMBLED
ENERGY SOLUTIONS INTERNATIONAL • WEST ST PAUL, MN • WWW.ESILIGHTING.COM • (651) 268 - 6060

